

product parameters

X-4U530

- 4U Rack-Mounted Chassis
- 3 12038 hot-swappable fans
- 11 full-height PCI/PCIe expansion slots
- 1+1 Redundant Power Supply



EEB(15"*13")/EATX(12"*13")/CEB(12"*10.5")

ATX(12"*9.6")/Micro ATX(9.6"*9.6")/Mini-ITX(6.7"*6.7")

Rack-Mounted Chassis

*产品升级，具体以实物为准。



Dimensions	L530mm*W450mm*H177mm(including the width of the ears is 482MM)
Material	SGCC1.0mm
Front Panel Interfaces	1 power switch, 1 restart switch, 1 network indicator light, 1 system fault light, 2 USB 3.0
Heat Dissipation System	Supports intelligent temperature control, comes with 3 standard 12038 hot-swappable fans, and has 2 reserved 8038 fan bays at the rear panel
Compatible Motherboard	EEB(15"*13")/EATX(12"*13")/CEB(12"*10.5")/ATX(12"*9.6")/Micro ATX(9.6"*9.6")/Mini-ITX(6.7"*6.7")
Compatible Power Position	1+1 Redundant Power Supply
HDD Bay	4 units of 3.5" HDDs and 2 units of 2.5" HDDs/SSDs
Applicable hard drive	Compatible with 3.5"/2.5" SAS and SATA hard drives
HDD Backplane	12Gb/s SAS data backplane, supporting SGPIO
Expansion Slot	11 full height PCI/PCIe expansion slots
Front Mask	Optional
Slide Rail	Optional
Packaging Details	Carton Box with PE foam and polybag
Package Size	D660*W540*H270mm
Single gross weight	12KG