

product parameters

X-2U430

- 2U Rack-Mounted Chassis
- 2U power supply/CRPS redundant power supply
- 3 8035 hot-swappable fans
- 7 half-height PCI/PCIe expansion slots



EATX(12"*13")/CEB(12"*10.5")/ATX(12"*9.6")
Micro ATX(9.6"*9.6")/Mini-ITX(6.7"*6.7")

Rack-Mounted Chassis

*产品升级，具体以实物为准。



D i m e n s i o n s	L430mm*W435mm*H90mm
M a t e r i a l	SGCC1.0mm
Front Panel Interfaces	1 power switch, 1 restart switch, 1 network indicator light, 1 system fault light, 2 USB 3.0
Heat Dissipation System	Supports intelligent-temperature control,3 pcs 8038 hot-swap fans
C o m p a t i b l e M o t h e r b o a r d	EATX(12"*13")/CEB(12"*10.5")/ATX(12"*9.6")/Micro ATX(9.6"*9.6")/Mini-ITX(6.7"*6.7")
Compatible Power Position	2U power supply/CRPS redundant power supply
H D D B a y	4 x 2.5" SATA drives
Surface Treatment	The front panel and mounting ears are coated with black paint, the handles feature an oxidized silver finish, and the cabinet along with its accessories retain the natural finish of steel sheets
HDD Backplane	6Gb/s SAS data backplane, supporting SGPIO
Expansion Slot	7 half-height PCI/PCIe expansion slots (vertical mounting)
Slide Rail	Optional
CPU Cooler Height Limit	70mm
Packaging Details	Carton Box with PE foam and polybag
Package Size	D540*W530*H175mm
Single gross weight	14KG